

NOCTUA NF-A14 industrialPPC-24V-2000 SP IP67 PWM 140x140x25mm Fan

Conceived for industrial heavy-duty applications that require enhanced cooling performance and advanced ingress protection, the NF-A14 industrialPPC (Protected Performance Cooling) is a ruggedised high-speed version of the award-winning retail model. The 24V SP variant uses Noctua's new NE-FD5 high-efficiency single-phase motor driver IC in order to support 24Vbased industrial and automotive applications. Its sophisticated inrush current suppression and extreme electrical robustness with extended burst and surge immunity allow it to operate safely in sensitive or hostile electronic environments. Thanks to the outstanding aerodynamic efficiency of the NF-A14 design and the high-performance single-phase motor, the industrialPPC SP version provides superior airflow and pressure capacity while keeping noise and power consumption at a moderate level as against comparable high-speed fans. While its fibre-glass reinforced polyamide construction and certified water and dust protection make the NF-A14 industrialPPC suitable for operation in challenging surroundings, the renowned SSO2 bearing technology guarantees an MTTF of over 150,000hrs. Topped off with Noctua's trusted reliability and 6-year manufacturer's warranty, the NF-A14 industrialPPC is an ideal choice for highly demanding applications that require superior flow rates and ultimate dependability.

Size	140x140x25 mm
Bearing	SSO2
Blade geometry	A-Series with Flow Acceleration Channels
Frame technology	AAO (Advanced Acoustic Optimisation)
IP rating / connector	67 / 3-pin
Input power / voltage	2.4 W / 24 V
MTTF	> 150,000 h

Max. rotational speed 12V (+/-10%)	1100 RPM
Max. rotational speed 24V (+/-10%)	2000 RPM
Max. airflow	182.5 m³/h
Max. acoustical noise	31.5 dB(A)
Max. static pressure	4.18 mmH ₂ 0

 Noctua NF-A14 industrialPPC-24V-2000 SP

 IP67 PWM

 EAN

 9010018100594

 UPC

 841501110597

 Packaging dimensions (HxWxD)

 200x190x34 mm

Weight incl. packaging

315 g Warranty

6 years

Packaging unit 20 pcs

Packaging dimensions / unit (HxWxD) 410x400x200 mm

Weight incl. packaging / unit 7.30 kg

Scope of delivery Fan, 4 fan screws

