

# NF-A14 PWM

## Noctua NF-A14 PWM Premium Fan



The NF-A14 is a premium quality quiet 140mm fan with a square frame that complies with Noctua's AAO (Advanced Acoustic Optimisation) standard. Its square shape and 140mm mounting holes (124.5mm spacing) make it ideal for use on watercooling radiators or as an upgrade for 140mm case fans. Featuring sophisticated aerodynamic design measures such as Flow Acceleration Channels, the NF-A14 further improves the renowned quiet cooling performance of the award-winning NF-P14. The PWM version sports Noctua's custom designed NE-FD1 IC for fully automatic speed control via 4-pin fan headers and comes with a Low-Noise-Adaptor to reduce the maximum speed during PWM control from 1500rpm to 1200rpm. Its performance-oriented 1500rpm top speed and comprehensive speed control options make the NF-A14 PWM an elite choice for users who strive to strike a perfect balance between excellent cooling capacity and superb quietness of operation, be it on watercooling radiators, on heatsinks or in case ventilation.

### Succeeding the award-winning NF-P14

Noctua's NF-P14 fan has become a default-choice among PC enthusiasts looking for a premium quality quiet 140mm fan. Thanks to its thoroughgoing aerodynamic optimisations, the NF-A14 provides higher static pressure and an even better airflow/noise ratio than its much acclaimed predecessor.

### Square 140mm frame

The NF-A14's square 140mm frame with 140mm mounting holes (124.5mm spacing) makes it a premium grade replacement for common 140mm case fans and perfect for use on 140mm water cooling radiators, where its square shape will ensure full coverage and best pressure performance.

### Flow Acceleration Channels

The NF-A14 impeller features suction side Flow Acceleration Channels. By speeding up the airflow at the crucial outer blade regions, this measure reduces suction side flow separation and thus leads to better efficiency and lower vortex noise.

### AAO Frame

Noctua's AAO (Advanced Acoustic Optimisation) frames feature integrated anti-vibration pads as well as Noctua's proprietary Stepped Inlet Design and Inner Surface Microstructures, both of which further refine the fan's performance/noise efficiency.

### Custom designed PWM IC with SCD

Supporting fully automatic PWM speed control, the NF-A14 PWM uses Noctua's novel, custom designed NE-FD1 PWM IC that integrates Smooth Commutation Drive (SCD) technology. By providing smoother torque impulses, SCD suppresses PWM switching noises and thus makes the fan quieter at low speeds.

### Stepped Inlet Design

Noctua's Stepped Inlet Design adds turbulence to the influx in order to facilitate the transition from laminar flow to turbulent flow, which reduces tonal intake noise, improves flow attachment and increases suction capacity, especially in space restricted environments.

### Low-Noise Adaptor

The NF-A14 PWM is supplied with a Low-Noise Adaptor (L.N.A.) that reduces the maximum fan speed from 1500 to 1200rpm. The L.N.A. can be used either to run the fan at a fixed speed of 1200rpm or to cap the maximum speed when using automatic PWM control.

### 6 years manufacturer's warranty

Noctua fans are renowned for their impeccable quality and outstanding longevity. Like all Noctua fans, the NF-A14 features an MTTF of more than 150,000 hours rating and comes with a full 6 years manufacturer's warranty.

### LOGISTIC DATA

Product name  
Noctua NF-A14 PWM

EAN  
4716123314981

UPC  
842431014337

Packaging dimensions (HxWxD)  
242x174x37 mm

Weight incl. packaging  
370 g

Warranty  
6 years

Packaging unit  
40 pcs

Packaging dimensions / unit (HxWxD)  
440x400x390 mm

Weight incl. packaging / unit  
15.20 kg

### SCOPE OF DELIVERY

NF-A14 PWM premium fan

Low-Noise Adaptor (L.N.A.)

4-pin y-cable

30cm extension cable

4x anti-vibration mounts

4x fan screws

### SPECIFICATIONS

Dimensions	140x140x25 mm
Bearing	SS02
Blade geometry	A-Series with Flow Acceleration Channels
Max. input power / voltage	1.56 W / 12 V
MTTF	> 150,000 h

NF-A14 PWM	w/o adaptor	with L.N.A.
Max. rotational speed (+/-10%)	1500 RPM	1200 RPM
Max. airflow	140.2 m³/h	115.5 m³/h
Max. acoustical noise	24.6 dB(A)	19.2 dB(A)
Max. static pressure	2.08 mmH <sub>2</sub> O	1.51 mmH <sub>2</sub> O