


#### Highly optimised impeller with Bevelled Blade Tips

Thanks to its further refined blade geometry with extended leading edges and Bevelled Blade Tips, the NF-S12B achieves up to 10% more airflow and static pressure than its much acclaimed predecessor at the same noise level



#### 2 speed settings for maximum quietness

Providing 700 and 500 rpm speed settings via the supplied adaptor, the ULN (Ultra-Low-Noise) version is tailor made for serious silent enthusiasts who demand super-slow running speeds and utmost quietness of operation.



#### Smooth Commutation Drive 2

The latest version of Noctua's advanced SCD drive system ensures superb running smoothness by eliminating torque variations and switching noises.



#### SSO - Bearing

Noctua's time-tested SSO-Bearing technology has become synonymous with supremely quiet operation and exceptional long-term stability.

Size	120 x 120 x 25 mm
Bearing	SSO-Bearing
Blade Geometry	NF-S12B Blade Design with BBT
Input Power	0.6 W
Input Current	0.05 A
Voltage Range	12 V
MTBF	> 150.000 h

Specifications	Standard	with U.L.N.A.
Rotational Speed +/-10%	700 RPM	500 RPM
Airflow	56.9 m³/h	38.2 m³/h
Acoustical Noise	6.8* dB(A)	5* dB(A)
Static Pressure	0.44 mmH <sub>2</sub> O	0.23 mmH <sub>2</sub> O

\*extrapolated values

#### Product **Noctua NF-S12B ULN**

Warranty  
**6 Years**

Packaging Type Pcs./Colli  
**Retail 40**

#### Scope of Delivery

- Ultra-Low-Noise Adaptor(U.L.N.A.)
- 4 Vibration Compensators
- 3:4-Pin Adaptor
- Screws