Noctua NH-D9L D-Type Tower Cooler





LOGISTIC DATA

Product name

Noctua NH-D9L

4716123315582

842431012487

Packaging dimensions (HxWxD)

118x115x118 mm

Weight incl. packaging

1198 g

Warranty

6 years Packaging unit

Packaging dimensions / unit (HxWxD)

490x380x390 mm

Weight incl. packaging / unit

15.90 kg

The NH-D9L is a premium grade dual tower CPU cooler that has been designed to provide excellent quiet cooling performance at a height of only 110mm. Its comparably low profile (15mm lower than classic 9am tower coolers such as the NH-U9S) doesn't only quarantee full 3U compliance but also makes the NH-D9L ideal for compact HTPC and Small Form Factor cases that have airflow paths parallel to the mainboard. Thanks to its 95x95mm footprint, the NH-D9L clears the RAM and PCIe slots on all Intel based and most AMD based ITX mainboards. The induded NF-A9 premium fan supports automatic speed control via PWM for outstanding quietness of operation and a second, optional NF-A9 fan can be added for further improved performance in dual fan mode. Topped off with the trusted, pro-grade SecuFirm2™ multi-socket mounting system, Noctua's proven NT-H1 thermal compound and full 6 years manufacturer's warranty, the NH-D9L forms a highly compact premium package for space-restricted applications.

Low-profile tower design for better airflow efficiency

While most low-profile coolers blow air towards the motherboard, the NH-D9L is a tower style cooler that bows parallel to the mainboard, which allows for superior airflow efficiency in cases with front intake and rear exhaust fans that create an airflow path parallel to the mainboard.

3U compatibility

Whereas classic 9cm coolers with up to 125mm height fit 4U rack mount cases, the NH-D9L's reduced height of 110mm allows it to also fit 3U chassis. This makes it ideal for noise-sensitive 3U applications in fields such as audio or video processing.

100% compatibility with PCle cards on mini-ITX

Many Intel LGA115x based mini-ITX mainboards have the PCIe slot sitting right next to the 95x95mm socket zone. While larger coolers that exceed this zone are likely to block the PCIe slot, the 95x95xmm sized NH-D9L provides full compatibility with PCIe cards, be it on ATX, microATX or ITX.

6-year manufacturer's warranty

Noctua products are renowned for their impeccable quality and outstanding longevity. Like all Noctua fans, the supplied NF-A9's feature an MTTF rating of more than 150,000 hours and the entire NH-D9L package comes with a full 6-year manufacturer's warranty.

SCOPE OF DELIVERY

1x NH-D9L Heatsink 1x NF-A9 PWM premium fan 1x Low-Noise Adaptor (L.N.A.) 1x NT-H1 thermal compound 1x SecuFirm2™ mounting kit Installation-kit for second NF-A9 fan (optional)

NH-D9L HEATSINK SPECIFICATIONS

| Socket compatibility | Intel LGA115x (LGA1150, LGA1151, LGA1155, | |
|---------------------------|--|--|
| | LGA1156), LGA1200, LGA1700 (LGA17xx family), | |
| | LGA20xx (LGA2066, LGA2011-0 & LGA2011-3 | |
| | Square ILM) & AMD AM2, AM2+, AM3, AM3+, | |
| | AM4, FM1, FM2, FM2+ (backplate required) | |
| Dimensions | 110x95x95 mm | |
| Dimensions with NF-A9 PWM | 110x95x95 mm | |
| Weight | 428 g | |
| Weight with NF-A9 PWM | 531 g | |
| Material | Copper (base and heat-pipes), aluminium (cooling | |
| | fins), soldered joints & nickel plating | |
| Fan compatibility | 92x92x25 mm | |
| | | |

NF-A9 PWM FAN SPECIFICATIONS

| Dimensions | 92x92x25 mm | |
|-----------------------------------|--|-------------------------|
| Connector | 4-pin PWM | |
| Bearing | CCUJ | |
| Blade geometry | A-Series with Flow Acceleration Channels | |
| Frame technology | AAO | |
| Max. input power | 1 2 W | |
| Voltage | 12 V | |
| MTTF | > 150,000 h | |
| NF-A9 PWM | without adaptor | with L.N.A. |
| Max. rotational speed $(+/-10\%)$ | 2000 RPM | 1550 RPM |
| Max. airflow | 78.9 m³/h | 62.6 m³/h |
| Max. acoustical noise | 22.8 dB(A) | 16.3 dB(A) |
| Max. static pressure | 2.28 mmH ₂ 0 | 1.53 mmH ₂ 0 |

