Noctua NH-D9L D-Type Tower Cooler

NH-D9L





The NH-D9L is a premium grade dual tower CPU cooler that has been designed to provide excellent quiet cooling performance at a height of only 110mm. Its comparably low profile (15mm lower than classic 9cm tower coolers such as the NH-U9S) doesn't only guarantee full 3U compliance but also makes the NH-D9L ideal for compact HTPC and Small Form Factor cases that have airflow paths parallel to the mainboard. Thanks to its 95x95mm footprint, the NH-D9L clears the RAM and PCle slots on all Intel based and most AMD based ITX mainboards. The included NF-A9 premium fan supports automatic speed control via PWM for outstanding quietness of operation and a second, optional NF-A9 fan can be added for further improved performance in dual fan mode. Topped off with the trusted, pro-grade SecuFirm2 ™ multi-socket mounting system, Noctua's proven NT-H1 thermal compound and full 6 years manufacturer's warranty, the NH-D9L forms a highly compact premium package for space-restricted applications.

Low-profile tower design for better airflow efficiency

While most low-profile coolers blow air towards the motherboard, the NH-D9L is a tower style cooler that bows parallel to the mainboard, which allows for superior airflow efficiency in cases with front intake and rear exhaust fans that create an airflow path parallel to the mainboard.

3U compatibility

Whereas classic 9cm coolers with up to 125mm height fit 4U rack mount cases, the NH-D9L's reduced height of 110mm allows it to also fit 3U chassis. This makes it ideal for noise-sensitive 3U applications in fields such as audio or video processing.

Many Intel LGA115x based mini-ITX mainboards have the PCle slot sitting right next to the 95x95mm socket zone. While larger coolers that exceed this zone are likely to block the PCle slot, the 95x95xmm sized NH-D9L provides full compatibility with PCle cards, be it on ATX, microATX or ITX.

6-year manufacturer's warranty

100% compatibility with PCIe cards on mini-ITX

Noctua products are renowned for their impeccable quality and outstanding longevity. Like all Noctua fans, the supplied NF-A9's feature an MTTF rating of more than 150,000 hours and the entire NH-D9L package comes with a full 6-year manufacturer's warranty.

SCOPE OF DELIVERY

Packaging dimensions / unit (HxWxD) 490x380x390 mm

Weight incl. packaging / unit 15.90 kg

LOGISTIC DATA

4716123315582

842431012487

Packaging dimensions (HxWxD)

118x115x118 mm

Weight incl. packaging 1198 g

Warranty

6 years

Packaging unit

Product name
Noctua NH-D9L

NH-D9L Heatsink

NF-A9 PWM premium fan

Low-Noise Adaptor (L.N.A.)

NT-H1 thermal compound

SecuFirm2™ mounting kit

Installation-kit for second NF-A9 fan (optional)

NH-D9L HEATSINK SPECIFICATIONS

Contrat community like	AMD AMA AME 8 1-1-110A30E3 10A3700	
Socket compatibility	AMD AM4, AM5 & Intel LGA1851, LGA1700,	
	LGA1200, and LGA115x (LGA1150, LGA1151,	
	LGA1155, LGA1156)	
Dimensions	110x95x95 mm	
Dimensions with NF-A9 PWM	110x95x95 mm	
Weight	428 g	
Weight with NF-A9 PWM	531 g	
Material	Copper (base and heat-pipes), aluminium (cooling	
	fins), soldered joints & nickel plating	
Fan compatibility	92x92x25 mm	

NF-A9 PWM FAN SPECIFICATIONS

Dimensions	92x92x25 mm	
Connector	4-pin PWM	
Bearing	SS02	
Blade geometry	A-Series with Flow Acceleration Channels	
Frame technology	AAO	
Max. input power	1.2 W	
Voltage	12 V	
MTTF	> 150,000 h	
NF-A9 PWM	without adaptor	with L.N.A.
Max. rotational speed (+/–10%)	2000 RPM	1550 RPM
Max. airflow	78.9 m³/h	62.6 m³/h
Max. acoustical noise	22.8 dB(A)	16.3 dB(A)
Max. static pressure	2.28 mmH ₂ 0	1.53 mmH ₂ 0

