www.noctua.at



# NOCTUA NH-U12S REDUX 120MM SINGLE TOWER CPU COOLER

True to the spirit of Noctua's redux line, the NH-U12S redux is a streamlined, accessibly priced version of the iconic NH-U12S that has established itself as a benchmark for slim, highly compatible 120mm CPU coolers. The redux version uses the same proven heatsink layout that guarantees 100% compatibility with tall RAM modules as well as excellent case and PCle compatibility. Thanks to the popular NF-P12 redux-1700 PWM fan with automatic speed control, it provides high performance under load and runs whisper-quiet at idle. At the same time, Noctua's renowned, professional SecuFirm2<sup>™</sup> mounting system and the pre-applied NT-H1 thermal compound make installation child's play. Backed up with Noctua's trusted 6-year manufacturer's warranty, the NH-U12S redux is a smart, affordable choice for a quiet, high-quality 120mm cooler.

#### Based on the award-winning NH-U12S

The NH-U12S redux is based on Noctua's proven, premium-grade NH-U12S, which is widely recognised as one of the best slim 120mm single-tower coolers on the market. Having received more than 200 awards and recommendations from international hardware websites and magazines, the NH-U12S has convinced tens of thousands of customers around the globe.

#### Streamlined redux edition

Following the idea of Noctua's redux line, the NH-U12S redux takes the proven concept of the original NH-U12S and reduces it to its essential core: a quiet, quality-made 120mm cooler with streamlined accessories that is highly compatible and easy to install.

NH-U12S HEATSINK SPECIFICATIONS		
Socket compatibility	Intel LGA115x (LGA1150,	
	LGA1151, LGA1155, LGA1156),	
	LGA1200, LGA1700 (LGA17xx	
	family), LGA20xx (LGA2066,	
	LGA2011-0 & LGA2011-3 Square	
	ILM) & AMD AM2, AM2+, AM3,	
	AM3+, AM4, FM1, FM2, FM2+	
	(backplate required)	
Dimensions (with NF-P12 redux-1700 PWM)	158x125x45 mm (158x125x71 mm)	
Weight (with NF-P12 redux-1700 PWM)	550 g (710 g)	
Material	Nickel plated Copper (base and	
	heat-pipes), aluminium (cooling fins)	
Fan compatibility	120x120x25 mm, 140x150x25	
	mm & 140x140x25 mm	
	(with 120 mm holes)	

#### Proven NF-P12 fan with PWM

Specifically designed for pressure-demanding applications such as on heatsinks, the classic NF-P12 is a long-standing favourite among quiet cooling enthusiasts. The higher-speed 1700rpm redux line version supports PWM for automatic speed control, which allows it to run near silent most of the time and provide massive performance when necessary.

#### 6-year manufacturer's warranty

Noctua products are renowned for their impeccable quality and outstanding longevity. True to this legacy, the NH-U12S redux cuts no corners and, like all Noctua fans, the supplied NF-P12 redux features an MTTF rating of more than 150,000 hours. The entire package comes with a full 6-year manufacturer's warranty.

## NF-P12 REDUX-1700 PWM FAN SPECIFICATIONS

Dimensions	120x120x25 mm
Connector	4-pin PWM
Bearing	SSO
Blade geometry	Nine Blade Design with VCN
Max. input power	1.08 W
Voltage	12 V
MTTF	> 150,000 h

NF-P12 redux-1700 PWM	without adaptor
Max. rotational speed (+/-10%)	1700 RPM
Max. airflow	120.2 m³/h
Max. acoustical noise	25.1 dB(A)
Max. static pressure	2.83 mmH <sub>2</sub> 0

### LOGISTIC DATA

Product name Noctua NH-U12S redux

9010018000207

UPC

Packaging dimensions (HxWxD 202x144x121 mm

Waight incl. packaging

1169 g

6 years

Packaninn ur

12 pcs

Packaging dimensions / unit (HxWx[ 420x350x390 mm

Weight incl. packaging / un 14.98 kg

# SCOPE OF DELIVERY

NH-U12S redux heatsink

- NF-P12 redux-1700 PWM fai
- 4x NA-AVP1 chromax.gre anti\_vibration\_pads
- Fan mounting clips (one pair)
- NT-H1 high-grade thermal compound
- (pre-applied)
- SecuFirm2<sup>™</sup> mounting kit

