



HOME



NV-SPH1

NV-PS1 230/115V 12V
NV-FH2 8

12V PC

NV-FH2

Output connectors	8x 4-pin PWM
Input connectors	1x 5.5mm [outer diameter] / 2.1mm [inner diameter] barrel connector, 1x 4-pin PWM
Max. power via barrel conector input	60 W
Max. power via 4-pin PWM input	22 W
Operating voltage	5-24 V
Operating temperature	-40°C to +60°C
Flammability class	UL-94 V-0
Safety standards	EN 62368-1, EN 55035, EN 55032, UL-62368
Certifications	CE, UKCA, UL
Size	93x62x12.5mm (without cover) / 93x62x19mm (with cover)
Weight	47 g
Fan compatibility	All Noctua 24V, 12V, and 5V fans, many third party fans
Warranty	6 years

NV-PS1

	90~264 V
	47~63 Hz
	0.075 W
	II
	0~40 °C
	8~90 %
	EN 60950-1:2006 + A11 + A1 + A12 + A2, EN 62368-1, IEC 62368-1:2014, UL 60950-1 (2nd Edition), CAN/CSA C22.2 No.
EMC	EN 55032 Class B, FCC Part 15 Subpart B Class B
	C 7/16 A NEMA
	1-15 G BS 1363
	5.5mm /2.1mm NA-AC10 4
	PWM
	1.5 m
	6

SCOPE OF DELIVERY

- NV-FH2 fan hub
- NV-PS1 power supply
- EU socket adaptor (Type C)
- UK socket adaptor (Type G)
- US socket adaptor (Type A)