



NOCTUA NA-HC3 chromax.black.swap

INSTALLATION MANUAL

This document includes some instructions for installing your NA-HC3 chromax.black.swap heatsink cover.

Should you have any further questions, our support team (support@noctua.at) will be glad to assist you at any time.

Please also have a look at the regularly updated FAQs on our website: http://www.noctua.at/faqs

This document is also available in other languages at the following URL: http://www.noctua.at/manuals



Scan this code to display multi-lingual manuals on your mobile phone.



Caution

The covers increase the height of the heatsink by 5mm (from 160 to 165mm) and the width by 3mm (from 150mm to 153mm). Please make sure that your case offers sufficient clearance and that the covers don't make contact with any other components such as PCIe cards!

If your CPU cooler is not yet installed, please first install the heatsink and attach the fan(s) to the heatsink as described in the cooler manual.





3 Choose two colour inlays, remove the protective films and put them into the covers.





Warranty and Support

Even with high-grade products and strict quality control, the possibility of defects cannot be eliminated entirely. Therefore, we aim at providing the highest possible level of reliability and convenience by offering a warranty period of 6 years and direct, fast and straightforward RMA service.

Should you encounter any problems with your NA-HC3 chromax.black.swap heatsink cover, please don't hesitate to contact our support team (support@noctua.at).